

Terminal Tractor/Yard Spotter

Used Yard Spotter Tacoma - Tow tractors, also called tow tugs or towing tractors are popular for moving loads horizontally in airports, arenas, warehouses, manufacturing plants and other large buildings. These machines can tow numerous trailers in a train or snake-like formation. Some are designed specifically to tow large aircraft in order to position them into and out of airport terminals and hangars. The tractive effort concept is how loads move from place to place. Tractive effort refers to the total amount of traction a vehicle deploys on the ground. Tractive effort says that the heavier the load, the more tractive effort is required. The unit works by lifting a part of the load while it is towing; however, the load's wheels stay on the ground. The load is partially lifted by use of the tow tractor's hydraulic mast which is specifically designed to produce downforce on the drive wheel immediately beneath it, increasing the tractive effort. Traction allows the machine to deliver very large and heavy loads. Types of Tow Tractors Two types of towing tractors include heavy-duty tow tractors and load carriers. Load Carriers Many industries including airport baggage divisions, manufacturing, parcel transportation and e-commerce rely on moving items of various sizes to and from different locations. Tow tugs or load carrier tow tractors are excellent for these jobs as they can maneuver single items stacked on wheeled platforms for streamlined transport. These load carrier tow tractors fall under the material handling equipment industry which includes other machines such as pallet jacks, forklifts and cranes. These units only transport loads at ground level and do not lift or lower items from shelving or off the ground. In order to be ready for transport, items must be secured on a wheeled platform or already on wheels to use the tow tractor. The wheeled platforms are called bogies, trollies or skates. The tow tractor attaches to the trolley and operates similarly to how train cars are attached to a locomotive. Typically, the tow tug features a steel coupling male-end that attaches to a female-end on the trolley's front. Trollies move in a train-like system thanks to the male-end steel coupling on the back which can connect to numerous units and allow a single tug to transport them. Tow tractors with a train of trollies enable a wider range in the type of items that can be transported and in the types of conditions they can be transported. Different trolley types are on the market to facilitate better transportation customization. Many trollies can be connected since they are compatible with one another. This means several different types of trollies can be used in a single train allowing greater flexibility for operations. An additional benefit of operating with load carrier tow tractors as opposed to forklifts is the unobstructed view offered by a tow tractor, increasing the safety of work areas. Further, load carrier tow tractors tow their trollies behind them in a forward-only direction which decreases the safety concerns created by forklifts operating in reverse. This design is excellent for locations that have a high level of safety such as manufacturing locations and airports. Towing many items at once saves time and money compared to relying on forklifts to move single things. Tugs are simple to move and provide a safe transport option. A key benefit of these units is that typically, the operator doesn't need a license. Tow tractor operators do not need licenses since they don't lift loads off of the ground. There are three subtypes of load carrier tow tractors: 1. Pedestrian; 2. Stand-in; and 3. Rider-seated. Pedestrian Tow Tractors A pedestrian tow tractor, also referred to as an electric tug, electric tugger, electric hand tug or tow tractor, is a walk-behind machine designed for easy movement of wheeled loads. These machines are simple to use, extremely maneuverable and very compact. Stand-in Tow Tractors Popular for industries that conduct order picking and horizontal transport for manufacturing, the stand-in tow tractors are the best design. These units deliver a secure driver platform and deliver a smaller footprint compared to the rider-seated models. Rider-Seated Tow Tractors The rider-seated tow tractors are similar to the stand-in tow tractors with the exception they provide a seated platform for the driver. Rider-seated models are used for moving loads longer distances. They are popular for airport luggage transport to move checked baggage from the check-in counter to the aircraft parked at the terminal. These rider-seated options help to decrease driver fatigue allowing for greater efficiency. Heavy Duty Tow Tractors The pushback

concept is commonly used in aviation for cargo and large passenger planes. Pushback refers to the process of pushing an aircraft back from an airport terminal by some means other than the aircraft's own power. Heavy-duty tow tractors are known as pushback tugs or pushback tractors complete this task. Pushback tugs feature a low-profile enabling them to travel under the aircraft's nose for easy attachment. Because of the added heavy weight of the aircraft, these tow tractors must be heavy enough to retain enough traction on the ground in order to move the aircraft. A common tractor for moving large aircraft can weigh in up to fifty-four tons. Their driver's cab has the ability to be lowered and raised for increased visibility during reversing. While the vehicle is referred to as a pushback tug or pushback tow tractor, it is also used to tow aircraft in areas where taxiing the aircraft is not practical or safe, such as moving large aircraft in and out of maintenance hangars. There are two subtypes of pushback tow tractors: 1. Conventional; and 2. Towbarless.

Conventional Pushback Tow Tractors Conventional tugs use a tow bar to connect the tug to the nose landing gear of the aircraft. The tow bar is laterally fixed at the nose landing gear; however, it is possible to make height adjustments with slight vertical movements. The tow bar is able to pivot vertically and laterally at the end that connects to the tug. In this manner, the tow bar acts as a large lever to rotate the nose landing gear. Each aircraft type has a unique tow fitting so the towbar also acts as an adapter between the standard-sized tow pin on the tug and the type-specific fitting on the aircraft's landing gear. On heavy towbars for large aircrafts, the towbar rides on its own wheels when not connected to an aircraft. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar can be connected at the front or the rear of the tractor, depending on whether the aircraft will be pushed or pulled.

Towbarless Pushback Tow Tractors Towbarless tractors do not use a towbar; they scoop up the nose landing gear and lift it off the ground, allowing the tug to maneuver the aircraft. This design facilitates higher speeds greater aircraft control and can eliminate the necessity of having a worker inside of the cockpit to apply the brakes. As there is no need to maintain numerous towbars, simplicity is the main advantage of this unit. By connecting the tug directly to the aircraft's landing gear tug operators have better control and responsiveness when maneuvering.